

PANEL CUT-OUT		
Z	Y	X
0.70~1.25	12.90~13.10	18.9~19.1
1.25~2.00	12.90~13.10	19.1~19.2
2.00~3.00	12.90~13.10	19.3~19.4

Rating:

CQC 6(4)A 250V AC T85
6A/125A 250VAC
UL cUL 10A 125V AC/6A 250V AC
VDE 6(4)A 250V AC T85
KC 6(4)A 250V AC T85

Circuit Diagram: 3P ON-OFF

Terminal Strength: $\geq 80N$



Electrical life: ≥ 10000 cycles

Withstand Voltage: Withstand Voltage:1800VAC 1min
Terminals to Button:3000VAC 1min

Leakage Current: 1mA

Current resistance: $\leq 50m\Omega$ (initial)

Insulation resistance: $\geq 100M\Omega$

A4				普通公差:	 东莞市朗伦电子制品有限公司 Dongguan langlun electronic products Co., Ltd								
A3				COMMON TOLERANCE:		单位	mm	投影		品名	跷板开关	比例	2:1
A2				UP TO 5		± 0.20	UNIT		核 对	吴路方	型号	3K601B-101N011RB	
A1				ABOVE 5 TO 30		± 0.30	绘图	朱文林	核 对	吴路方	MODEL NO.	3K601B-101N011RB	
				ABOVE 30	± 0.50	DRAWN BY		核 准	周培雷	图号	3K601B-101N011RB		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	$\pm 5^\circ$	日期	2012.11.14	APPROVAL BY		DWG NO.			