

Rating:  
 CQC 6A 250V AC T85  
 UL cUL 10A 125V AC / 6A 250V AC  
 VDE 6(4)A 250V AC T85/55  
 KC 6(4)A 250V AC

Circuit Diagram: 2P ON-OFF

Terminal Strength:  $\geq 80N$

Electrical life:  $\geq 10000$  cycles



Withstand Voltage: Withstand Voltage:1800VAC 1min  
 Terminals to Button:3000VAC 1min

Leakage Current: 1mA

Current resistance:  $\leq 50m\Omega$ (initial)

Insulation resistance:  $\geq 100M\Omega$

PANEL CUT-OUT		
Z	Y	X
0.70~1.25	6.50~6.70	18.9~19.1
1.25~2.00	6.50~6.70	19.1~19.2
2.00~3.00	6.50~6.70	19.3~19.4

A4				普通公差:	 <b>东莞市朗纶电子制品有限公司</b> <b>Dongguan langlun electronic products Co., Ltd</b>							
A3			COMMON TOLERANCE:	单位		mm	投影		品名	跷板开关	比例	2:1
A2			UP TO 5	$\pm 0.20$		UNIT	核 对	吴路方	型号			
A1			ABOVE 5 TO 30	$\pm 0.30$		绘图	朱文林	核 对	吴路方	型号	3K601D1-1010019BB	
			ABOVE 30	$\pm 0.50$	DRAWN BY		核 准	周培雷	图号	3K601D1-1010019BB		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	$\pm 5^\circ$	日期	2012.11.14	核 准	周培雷	图号	3K601D1-1010019BB	