



Rating:
 CQC 6A 250V AC T85
 UL cUL 10A 125V AC / 6A 250V AC
 VDE 6(4)A 250V AC T85/55
 KC 6(4)A 250V AC

Circuit Diagram: 4P ON-OFF
 Terminal Strength: ≥80N
 Electrical life: ≥10000 cycles
 Withstand Voltage: Withstand Voltage:1800VAC 1min
 Terminals to Button:3000VAC 1min
 Leakage Current: 1mA
 Current resistance: ≤50mΩ(initial)
 Insulation resistance: ≥100MΩ

PANEL CUT-OUT		
Z	Y	X
0.70~1.25	12.90~13.10	18.9~19.1
1.25~2.00	12.90~13.10	19.1~19.2
2.00~3.00	12.90~13.10	19.3~19.4

A4				普通公差:	 东莞市朗纶电子制品有限公司 Dongguan langlun electronic products Co., Ltd							
A3			COMMON TOLERANCE:	单位		mm	投影		品名	跷板开关	比例	2:1
A2			UP TO 5	±0.20		UNIT	mm	PROJECTED	PRODUCT NAME		SCALE	
A1			ABOVE 5 TO 30	±0.30		绘图	朱文林	核对	吴路方	型号		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	±5°	日期	2012.11.14	核准	周培雷	图号	3K601D1-2010011BB	
						DATE		APPROVAL BY		DWG NO.	3K601D1-2010011BB	