



Rating:  
 CQC 6(4)A 250V AC T85  
 6A/125A 250VAC  
 cULus 10A 125V AC/6A 250V AC  
 VDE 6(4)A 250V AC T85  
 KC 6(4)A 250V AC T85

Circuit Diagram: 2P ON-OFF

Terminal Strength:  $\geq 80N$

Electrical life:  $\geq 10000$  cycles

Withstand Voltage: Withstand Voltage:1800VAC 1min

Terminals to Button:3000VAC 1min

Leakage Current: 1mA

Current resistance:  $\leq 50m\Omega$ (initial)

Insulation resistance:  $\geq 100M\Omega$

工程部 PANEL CUT-OUT

A4				普通公差:	 3K-KAMING	东莞市朗纶电子制品有限公司								
A3				COMMON TOLERANCE:		Dongguan langlun electronic products Co., Ltd								
A2				UP TO 5		±0.20	单位	mm	投影		品名	跷板开关	比例	Free
A1				ABOVE 5 TO 30		±0.30	UNIT		PROJECTED		PRODUCT NAME			
				ABOVE 30	±0.50	绘图	朱文林	核对	吴路方	型号	3K601E-1010011BB			
				ANGULAR	±5°	DRAWN BY		CHECKED BY		MODEL NO.				
REV.	DATE	REVISION DESCRIPTION	ISSUE			日期	2012.11.14	核准	周培雷	图号	3K601E-1010011BB			
						DATE		APPROVAL BY		DWG NO.				