


PANEL CUT-OUT



Rating:
 CQC 6A 250V AC T105
 6A/125A 250VAC
 cULus 10A 125V AC/6A 250V AC
 VDE 6(4)A 250V AC
 KC 6(4)A 250V AC

Circuit Diagram: 3P ON-OFF-ON

Terminal Strength: $\geq 80N$

Electrical life: ≥ 10000 cycles




Withstand Voltage: Withstand Voltage: 1500VAC 1min

Terminals to Button: 3000VAC 1min

Leakage Current: 1mA

Current resistance: $\leq 50m\Omega$ (initial)

Insulation resistance: $\geq 100M\Omega$

A4				普通公差:	 3K-KAMING	东莞市朗纶电子制品有限公司								
A3				COMMON TOLERANCE:		Dongguan langlun electronic products Co., Ltd								
A2				UP TO 5		±0.20	单位	mm	投影		品名	跷板开关	比例	Free
A1				ABOVE 5 TO 30		±0.30	UNIT		核 对		PRODUCT NAME		图 号	
				ABOVE 30	±0.50	绘 图	朱文林	核 对	吴路方	MODEL NO.	3K601E-1030041BB			
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	±5°	日 期	2012.11.14	核 准	周培雷	DWG NO.	3K601E-1030041BB			