


Rating:
 CQC 6A 250V AC T85
 6A/125A 250VAC
 UL cUL 10A 125V AC/6A 250V AC
 VDE 6(4)A 250V AC T85/55
 KC 6(4)A 250V AC

Circuit Diagram: 6P ON-OFF
 Terminal Strength: $\geq 80N$
 Electrical life: ≥ 10000 cycles
 Withstand Voltage: Withstand Voltage:1800VAC 1min
 Terminals to Button:3000VAC 1min
 Leakage Current: 1mA
 Current resistance: $\leq 50m\Omega$ (initial)
 Insulation resistance: $\geq 100M\Omega$

PANEL CUT-OUT		
Z	Y	X
0.70~1.25	21.90~22.10	18.9~19.1
1.25~2.00	21.90~22.10	19.1~19.2
2.00~3.00	21.90~22.10	19.3~19.4

A4				普通公差:	 东莞市朗纶电子制品有限公司 Dongguan langlun electronic products Co., Ltd							
A3			COMMON TOLERANCE:	单位		mm	投影		品名	跷板开关	比例	1.5:1
A2			UP TO 5	± 0.20		UNIT	核 对	吴路方	PRODUCT NAME		SCALE	
A1			ABOVE 5 TO 30	± 0.30		绘 图	朱文林	核 对	吴路方	型号		3K601F1-201N016RB
			ABOVE 30	± 0.50	DRAWN BY		核 准	周培雷	MODEL NO.			
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	日期	2012.11.14	核 准	周培雷	DWG NO.		3K601F1-201N016RB	
				$\pm 5^\circ$	DATE		APPROVAL BY					