

Rating:

CQC 6A 250V AC T85
 6A/125A 250VAC
 UL cUL 10A 125V AC / 6A 250V AC
 VDE 6(4)A 250V AC T85/55
 kc 6(4)A 250V AC

Circuit Diagram: 4P ON-OFF

Terminal Strength: $\geq 80N$

Electrical life: ≥ 10000 cycles

Withstand Voltage: Withstand Voltage:1800VAC 1min



Terminals to Button:3000VAC 1min

Leakage Current: 1mA

Current resistance: $\leq 50m\Omega$ (initial)

Insulation resistance: $\geq 100M\Omega$

| PANEL CUT-OUT | | |
|---------------|-------------|-----------|
| Z | Y | X |
| 0.70~1.25 | 21.90~22.10 | 18.9~19.1 |
| 1.25~2.00 | 21.90~22.10 | 19.1~19.2 |
| 2.00~3.00 | 21.90~22.10 | 19.3~19.4 |

| | | | | | | | | | | | | | |
|------|------|----------------------|-------|-------------------|--|--|------------|-------------|---|---------|------------------|------------------|-------|
| A4 | | | | 普通公差: |  3K-KAMING | 东莞市朗纶电子制品有限公司 Dongguan langlun electronic products Co., Ltd | | | | | | | |
| A3 | | | | COMMON TOLERANCE: | | 单位 | mm | 投影 |  | 品名 | 跷板开关 | 比例 | 1.5:1 |
| A2 | | | | UP TO 5 | | ± 0.20 | UNIT | PROJECTED | 核 对 | 吴路方 | 型号 | 3K601F-2010011BB | |
| A1 | | | | ABOVE 5 TO 30 | | ± 0.30 | 绘图 | 朱文林 | CHECKED BY | 周培雷 | 图号 | 3K601F-2010011BB | |
| REV. | DATE | REVISION DESCRIPTION | ISSUE | ABOVE 30 | ± 0.50 | 日期 | 2012.11.14 | 核 准 | 周培雷 | DWG NO. | 3K601F-2010011BB | | |
| | | | | ANGULAR | $\pm 5^\circ$ | DATE | | APPROVAL BY | | | | | |