

PANEL CUT-OUT		
Z	Y	X
0.70~1.25	12.90~13.10	18.9~19.1
1.25~2.00	12.90~13.10	19.1~19.2
2.00~3.00	12.90~13.10	19.3~19.4

Rating:  
 CQC 6(4)A 250V AC T85  
 6A/125A 250VAC  
 cULus 10A 125V AC/6A 250V AC  
 VDE 6(4)A 250V AC T85  
 KC 6(4)A 250V AC

Circuit Diagram: 6P ON-ON

Terminal Strength:  $\geq 80N$


Electrical life:  $\geq 10000$  cycles



Withstand Voltage: Withstand Voltage:1500VAC 1min  
 Terminals to Button:3000VAC 1min

Leakage Current: 1mA

Current resistance:  $\leq 50m\Omega$ (initial)

Insulation resistance:  $\geq 100M\Omega$



A4				普通公差:	 <b>东莞市朗纶电子制品有限公司</b> <b>Dongguan langlun electronic products Co., Ltd</b>							
A3			COMMON TOLERANCE:	单位		mm	投影		品名	跷板开关	比例	1.5:1
A2			UP TO 5	$\pm 0.20$		UNIT		PROJECTED	PRODUCT NAME		SCALE	
A1			ABOVE 5 TO 30	$\pm 0.30$		绘图	朱文林	核对	吴路方	型号		
			ABOVE 30	$\pm 0.50$	DRAWN BY		CHECKED BY		MODEL NO.		3K601G-2020018BB	
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	$\pm 5^\circ$	日期	2012.11.14	核准	周培雷	图号	3K601G-2020018BB	
						DATE		APPROVAL BY		DWG NO.		