






Rating:  
 CQC 16(4)A 250V AC T85  
 UL cUL 16A 125V AC/16A 250V AC T125  
 VDE 16(4)A 250V AC T85

Circuit Diagram: 4P ON-OFF  
 Terminal Strength: ≥80N  
 Electrical life: ≥10000 cycles  
 Withstand Voltage: Withstand Voltage:1800VAC 1min  
 Terminals to Button:3000VAC 1min  
 Leakage Current: 1mA  
 Current resistance: ≤50mΩ(initial)  
 Insulation resistance: ≥100MΩ



PANEL CUT-OUT		
Z	Y	X
0.70~1.25	21.90~22.10	28.9~29.1
1.25~2.00	21.90~22.10	29.1~29.2
2.00~3.00	21.90~22.10	29.2~29.3

A4				普通公差:	 <b>东莞市朗纶电子制品有限公司</b> <b>Dongguan langlun electronic products Co., Ltd</b>							
A3			COMMON TOLERANCE:	单位		mm	投影		品名	跷板开关	比例	1.5:1
A2			UP TO 5	±0.20		UNIT			PRODUCT NAME		SCALE	
A1			ABOVE 5 TO 30	±0.30		绘图	朱文林	核对	吴路方	型号		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	±5°	日期	2012.11.14	核准	周培雷	图号	3K606-201N011CRB	