


P.C.B LAYOUT



CIRCUIT DIAGRAM

SPECIFICATIONS

Rating	DC 12V 50mA
Contact Resistance	150mΩ Max
Insulation Resistance	50MΩ Min
Operating Force	40 ±15gf
Life	50,000 cycles



MODEL	H (mm)
-	8.50
A	9.00
F	9.50
C	11.0

	PARTS	MATERIALS	Q'TY	FINISH
E	THERMINAL	PHOSPHOR BRONZE	4	Ag PLATED
D	CONTACT SPRING	PHOSPHOR BRONZE	1	Ag PLATED
C	COVER	PA46	1	BLACK
B	CASE	PPA	1	BLACK
A	KNOB	PA46	1	BLACK

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新MODLE	Jack	052115
1	新增高度选项	Jack	123114



东莞市朗纶电子制品有限公司  
Dongguan langlun electronic products Co., Ltd

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	SIZE
Jack Lu	05/21/15		SWITCH	A4
CHECKED BY:	DATE	FINISH	MODLE	VER
Jacky Chen	05/21/15		DETECTOR SWITCH(小方柄)	A2
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	05/21/15	1 : 1	3K- A20Sx-S246	
		SHEET NO.	PART NO.	
		1 of 1	3K- A20Sx-S246	