



Rating :
 5A 250V AC T105 UL cUL
 2.5A 250V AC VDE 3C KC
 Insert And Extract Force: 1.36kgf~6.8kgf
 Terminal Strength: ≥80N
 Operating Life: ≥5000 cycles
 Withstand Voltage: Between all terminals:2500VAC (50-60Hz)1min
 terminals to Base:3750V AC (50-60Hz)1min
 Leakage Current : 1mA
 Insulation Resistance: ≥100MΩ 500V DC

SECTION A-A



A4				普通公差	 3K-KAMING 东莞市朗纶电子制品有限公司 Dongguan langlun electronic products Co., Ltd	东莞市朗纶电子制品有限公司						
A3				COMMON TOLERANCE		Dongguan langlun electronic products Co., Ltd						
A2				UP TO 5		±0.20	单位	mm	投影	Ac Inlet C6型	比例	Free
A1				ABOVE 5 TO 30		±0.30	UNIT		PRODUCT NAME	Ac Inlet C6型	SCALE	Free
				ABOVE 30	±0.50	绘图	吴瑜	核对	品名	3K-6-4VS2S8 (G)		
				ANGULAR	±5°	DRAWN BY		CHECKED BY	型号	3K-6-4VS2S8 (G)		
REV.	DATE	REVISION DESCRIPTION	ISSUE			日期	2009.06.17	核准	图号	64VS2S8(G)		
						DATE		APPROVAL BY	DWG NO.			