



Insert And Extract Force:

Rating : 2.5A 250V AC VDE 3C

1.36kgf~6.8kgf

Terminal Strength: ≥80N

Operating Life: ≥5000 cycles

Withstand Voltage: Between all terminals:2500VAC (50-60Hz)1min  
terminals to Base:3750V AC (50-60Hz)1min

Leakage Current : 1mA

Insulation Resistance: ≥100MΩ 500V DC



A4				普通公差		<b>东莞市朗纶电子制品有限公司</b> <b>Dongguan langlun electronic products Co., Ltd</b>				
A3				COMMON TOLERANCE :		单位	投影	品名	Ac Inlet C8型	
A2				UP TO 5	±0.20	mm	第一角	PRODUCT NAME		
A1	2011.3.20	卡耳第二个位置由2.3mm修改为2.5mm,卡耳宽度由23.3mm修改为22.7mm	吴路方	ABOVE 5 TO 30	±0.30	绘图	核对	型号	3K-8-19AS1 (2)	
REV.	DATE	REVISION DESCRIPTION	ISSUE	ABOVE 30	±0.50	DRAWN BY	CHECKED BY	MODEL NO.		
				ANGULAR	±5°	日期	核准	图号	819AS1	
						DATE	APPROVAL BY	DWG NO.		