



器具插座	器具开关
Rating : 15A 250V AC T105 UL cUL 10A 250V AC VDE 3C KC Fuse : 250VAC 6.3A 2.5W Insert And Extract Force: 36kgf~6.8kgf Terminal Strength: ≥80N Operating Life: ≥5000 cycles Withstand Voltage: Between all terminals:2500VAC (50-60Hz) 1min terminals to Base:3750V AC (50-60Hz) 1min Leakage Current : 1mA Insulation Resistance: ≥100MΩ 500V DC	Rating: CQC 6A 250V AC T85 UL cUL 10A 125V AC / 6A 250V AC VDE 6(4)A 250V AC T85/55 KC 6(4)A 250V Circuit Diagram: 4P ON-OFF Terminal Strength: ≥80N Electrical life: ≥10000 cycles Withstand Voltage: Withstand Voltage:1800VAC 1min Terminals to Button:3000VAC 1min Leakage Current: 1mA Current resistance: ≤50mΩ(initial) Insulation resistance: ≥100MΩ



A4				普通公差	 3K-KAMING	东莞市朗纶电子制品有限公司 Dongguan langlun electronic products Co., Ltd							
A3				COMMON TOLERANCE :		单位	mm	投影		品名	Ac Inlet C14型	比例	Free
A2				UP TO 5		±0.20	UNIT		核对应	PRODUCT NAME		SCALE	
A1				ABOVE 5 TO 30		±0.30	绘图	吴瑜	核对应	MODEL NO.	3K-14-5F(1.5)+RS601D1-2010011BB-3A		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	±5°	日期	2012.02.10	核准	图号	145FRS601D2010011BB-3A			
						DATE		APPROVAL BY	DWG NO.				