






RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.

DIMENSIONS



PCB板安装孔图



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

1	额定负荷Rated laod	12V 2A AC
2	接触电阻Contact resistance	≤30m Ω
3	绝缘电阻Insulation resistance	≥100MΩ
4	耐压Witstand Voltage	AC 250V (50HZ) /1min
5	电器寿命Life	≥ 5000 cycle
6	动作力度Strength of action	5-50N You can customize it
7	环境温度The environment temperature	-15~75℃
8	相对湿度Relative humidity	≤95 % (40℃)
9		
10		
11		

NO	配件Accessories	材料名称Material	产地Place of origin	备注Note	WITHIN 1.5mm: ±0.1mm
1	上盖/基座Topcover/base	PBT	进口/国产Imports / domestic	黑/白Black/white	OVER 1.5mm: ±0.2mm
2	塑胶内件interior	PBT	进口/国产Imports / domestic	黑/白Black/white	
3	端子/拉伸件Terminals/stretchers	H62黄铜Brass	进口/国产Imports / domestic	CU/Ni/SN	
4	短针Short needle	H62黄铜Brass	进口/国产Imports / domestic	CU/Ni/SN	
5	中针 Middle Needle	H62黄铜Brass	进口/国产Imports / domestic	CU/Ni/SN	
6	长针Long needle	H62黄铜 Brass	进口/国产Imports / domestic	CU/Ni/SN	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE 3K-KAMING(LANG LUN) INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE 3K-KAMING(LANG LUN) INC.

UNITS

mm

MAT'L

SEE NOTE

FINISH

SEE NOTE

Q'TY



东莞市朗纶电子制品有限公司
Dongguan langlun electronic products Co., Ltd

TITLE:

PUSH SWITCH / VERTICAL

DR:

Ricky 2015/03/23

CHKD:

Ricky 2015/03/23

APPD:

PART NO.:

3K--3-03A

DWG NO.:

3K--3-03A

SCALE

4:1

SHEET

1/1

REV.

A

CUSTOMER

DRAWING

