





RoHS  
Compliant  
2002/95/EC

REV.	ECN.	NO.	APPD.

## DIMENSIONS




## ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

1	额定负荷Rated load	12V 0.5A DC
2	接触电阻Contact resistance	≤30m Ω
3	绝缘电阻Insulation resistance	≥100MΩ
4	耐压Withstand Voltage	AC 250V (50HZ) /1min
5	电器寿命Life	≥ 5000 cycle
6	动作力度Strength of action	5-50N You can customize it
7	环境温度The environment temperature	-15~75℃
8	相对湿度Relative humidity	≤95% (40℃)
9		
10		
11		

## PCB板安装孔图



NO	配件Accessories	材料名称Material	产地Place of origin	备注Note	WITHIN 1.5mm: ±0.1mm
1	上盖/基座Topcover/base	PBT	进口/国产Imports / domestic	黑/白Black/white	OVER 1.5mm: ±0.2mm
2	塑胶内件interior	PBT	进口/国产Imports / domestic	黑/白Black/white	
3	端子/拉伸件Terminals/stretchers	H62黄铜Brass	进口/国产Imports / domestic	CU/Ni/SN	
4	短针Short needle	H62黄铜Brass	进口/国产Imports / domestic	CU/Ni/SN	
5	中针 Middle Needle	H62黄铜Brass	进口/国产Imports / domestic	CU/Ni/SN	
6	长针Long needle	H62黄铜Brass	进口/国产Imports / domestic	CU/Ni/SN	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE 3K-KAMING(LANG LUN) INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE 3K-KAMING(LANG LUN) INC.

UNIT	mm
MAT'L	SEE NOTE
FINISH	SEE NOTE
Q'TY	



东莞市朗纶电子制品有限公司  
Dongguan langlun electronic products Co., Ltd

TITLE:	PUSH SWITCH / VERTICAL	PART NO.:	3K-6-01A
DR:	Ricky 2015/03/23	DWG NO.:	3K-6-01A
CHKD:	Ricky 2015/03/23	SCALE	4:1
APPD:		SHEET	1/1
		REV.	A
		CUSTOMER	DRAWING