





性能:

额定电流: 0.5A

额定电压: 50V

耐电压: 500V






接触电阻: 30mΩ

绝缘电阻: 800MΩ

工作温度: -20℃ ~ +85℃


塑件(材质): LCP BLACK, UL94V-0

插簧(材质): 磷青铜, 镀锡/镀金



适用扁平电缆

孔位	A	B	C
4	6.00	3.00	5.10
5	7.00	4.00	6.10
6	8.00	5.00	7.10
7	9.00	6.00	8.10
8	10.00	7.00	9.10
9	11.00	8.00	10.10
10	12.00	9.00	11.10
11	13.00	10.00	12.10
12	14.00	11.00	13.10
13	15.00	12.00	14.10
14	16.00	13.00	15.10
15	17.00	14.00	16.10
16	18.00	15.00	17.10
17	19.00	16.00	18.10
18	20.00	17.00	19.10
19	21.00	18.00	20.10
20	22.00	19.00	21.10
21	23.00	20.00	22.10
22	24.00	21.00	23.10
23	25.00	22.00	24.10
24	26.00	23.00	25.10
25	27.00	24.00	26.10
26	28.00	25.00	27.10
27	29.00	26.00	28.10
28	30.00	27.00	29.10
29	31.00	28.00	30.10
30	32.00	29.00	31.10
31	33.00	30.00	32.10
32	34.00	31.00	33.10
33	35.00	32.00	34.10
34	36.00	33.00	35.10
35	37.00	34.00	36.10



PCB LAYOUT



X. ± 0.3	X° ± 5°	UNITS	mm	NAME (INTENDED USE)	东莞市朗纶电子制品有限公司 Dongguan langlun electronic products Co., Ltd TITLE: 1.0mm FPC(双面接) 弯针(正脚) DWG NO.:
.X ± 0.25	.X° ± 2°	MAT'L		PART NO. (INTENDED USE)	
.XX ± 0.20	.XX° ± 1°	FINISH		1.0-B-nPW	
.XXX ± 0.10	.XXX° ± 0.5°	Q'TY		APPD:	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE 3K-KAMING (LANG LUN) INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE 3K-KAMING (LANG LUN) INC.				CHKD:	
				DR: huang sheng 2013/03/29	
				SCALE	SHEET
				1/1	1/1
				REV.	A