




Assembly Layout



Recommend PCB Layout

Circuit	Dimensions (mm)			Circuit	Dimensions (mm)		
	A	B	C		A	B	C
02	1.00	4.00	2.50	10	9.00	12.00	10.50
03	2.00	5.00	3.50	11	10.00	13.00	11.50
04	3.00	6.00	4.50	12	11.00	14.00	12.50
05	4.00	7.00	5.50	13	12.00	15.00	13.50
06	5.00	8.00	6.50	14	13.00	16.00	14.50
07	6.00	9.00	7.50	15	14.00	17.00	15.50
08	7.00	10.00	8.50	16	15.00	18.00	16.50
09	8.00	11.00	9.50	20	19.00	22.00	20.50

NO.	DESCRIPTION	QTY	MATERIAL	PLATING/COLOR
A	Insulator	1	LCP (UL94V-0)	Beige
B	Contacts	2~16	PhosphorBronze	Tin-plated
C	SolderTab	2	PhosphorBronze	Tin-plated

主要技术参数 Main Specifications

线 数 (Poles): 02 to 20
 接触电阻 (Contact resistance): $\leq 20m\Omega$
 绝缘电阻 (Insulation resistance): $\geq 100M\Omega$
 额定电压 (Rated voltage): 50V AC DC
 额定电流 (Rated current): 1.0A AC DC
 耐 电压 (Withstand Voltage): 500V AC/minute
 温度范围 (Temperature Range): $-25^{\circ}C \sim +105^{\circ}C$

UNITS mm		东莞市朗纶电子制品有限公司 Dongguan langlun electronic products Co., Ltd			
MAT'L		PART NO.(INTENDED USE) 1. 0-Q-nPWB		TITLE: SH1.0卧贴针座	
FINISH		APPD:		DWG NO.: 1. 0-Q-nPWB	
Q'TY PCS		CHKD:		DR: HU 2016.09.28	
		SCALE		SHEET	
		1/1		1/1	
		REV.		A	

