

主要技术参数 Main Specifications

- 线数 (Poles): 02 to 16
- 接触电阻 (Contact resistance): $\leq 20m\Omega$
- 绝缘电阻 (Insulation resistance): $\geq 1000M\Omega$
- 额定电压 (Rated voltage): 250V AC DC
- 额定电流 (Rated current): 3.0A AC DC
- 耐电压 (Withstand Voltage): 1000V AC/minute
- 温度范围 (Temperature Range): $-25^{\circ}C \sim +105^{\circ}C$

ITEM	COMPONENT	Q'TY	MATERIAL	FINISH
C	Solder Tab	2 PCS	Brass	Tin-plated
B	Contacts	n PCS	Brass	Tin-plated
A	HOUSING	1 PCS	LCP	UL 94V-0, COLOR:BEIGE

Circuit	Dimensions (mm)				Circuit	Dimensions (mm)			
	A	B	C	D		A	B	C	D
02	2.50	7.50	10.00	8.20	10	22.50	27.50	30.00	28.20
03	5.00	10.00	12.50	10.70	11	25.00	30.00	32.50	30.70
04	7.50	12.50	15.00	13.20	12	27.50	32.50	35.00	33.20
05	10.00	15.00	17.50	15.70	13	30.00	35.00	37.50	35.70
06	12.50	17.50	20.00	18.20	14	32.50	37.50	40.00	38.20
07	15.00	20.00	22.50	20.70	15	35.00	40.00	42.50	40.70
08	17.50	22.50	25.00	23.20	16	37.50	42.50	45.00	43.20
09	20.00	25.00	27.50	25.70					




UNITS	东莞市朗纶电子制品有限公司		
MAT'L	Dongguan langlun electronic products Co., Ltd		
FINISH	PART NO.(INTENDED USE)	TITLE:	
	APPD:	CHKD:	
Q'TY	DR:	DWG NO.:	
		SCALE	
		SHEET	REV.

X.± 0.3	X° ± 5°	FINISH	TITLE:		
.X± 0.25	.X° ± 2°			CHKD:	
.XX± 0.20	.XX° ± 1°				DWG NO.:
.XXX± 0.10	.XXX° ± 0.5°				

FINISH	PCS	TITLE:		
Q'TY			CHKD:	
				DWG NO.:

DR:	HU 2016.09.28	SCALE	
	SHEET		
			REV.



SCALE	SHEET	REV.
1/1	1/1	A