






Assembly Layout

主要技术参数 Main Specifications

- 线 数 (Poles) : 02P
接触电阻 (Contact resistance): $\leq 20\text{m}\Omega$
绝缘电阻 (Insulation resistance): $\geq 1000\text{M}\Omega$
额定电压 (Rated voltage): 150 V AC DC
额定电流 (Rated current): 1.0A AC DC
耐电压 (Withstand Voltage): 1000V AC/minute
温度范围 (Temperature Range) : $-25^{\circ}\text{C} \sim +105^{\circ}\text{C}$

NO.	DESCRIPTION	QTY	MATERIAL	PLATING/COLOR
A	Insulator	1	LCP (UL94V-0)	Beige
B	Contacts	2	PhosphorBronze	Tin-plated
C	Solder Tab	2	PhosphorBronze	Tin-plated



Board Layout

General Tolerance: ± 0.05



UNITS mm	东莞市朗纶电子制品有限公司 Dongguan langlun electronic products Co., Ltd			
MAT'L	PART NO.(INTENDED USE) 3.0-2P-F2MB-R	TITLE: 3.0-2P对接插座公座		
FINISH	APPD:	DWG NO.: 3.0-2P-F2MB-R		
Q'TY PCS	CHKD:	DR: HU 2016.09.28		
			SCALE 1/1	SHEET 1/1
			REV. A	

X.± 0.3	X°.± 5°
.X± 0.25	.X°.± 2°
.XX± 0.20	.XX°.± 1°
.XXX± 0.10	.XXX°.± 0.5°