




REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD



Electrical
 Temperature Range—Operating: -25°C~+85°C
 Material
 Housing: PA66(UL 94V-0)
 Applicable Terminal: FT39603-F2H
 Mates With: FWF50805,FWF50806Series.



Circuits (n)	Part No.	Dimensions(in/mm)	
		A	B
2	FHG50803-S02M2TB	.200(5.08)	.400(10.16)
3	FHG50803-S03M2TB	.400(10.16)	.600(15.24)
4	FHG50803-S04M2TB	.600(15.24)	.800(20.32)
5	FHG50803-S05M2TB	.800(20.32)	1.000(25.40)
6	FHG50803-S06M2TB	1.000(25.40)	1.200(30.48)
7	FHG50803-S07M2TB	1.200(30.48)	1.400(35.56)
8	FHG50803-S08M2TB	1.400(35.56)	1.600(40.64)
9	FHG50803-S09M2TB	1.600(40.64)	1.800(45.72)
10	FHG50803-S10M2TB	1.800(45.72)	2.000(50.80)
11	FHG50803-S11M2TB	2.000(50.80)	2.200(55.88)
12	FHG50803-S12M2TB	2.200(55.88)	2.400(60.96)

Ordering Information

FHG 508 03 — S XX M 2 T B
 1 2 3 4 5 6 7 8 9

1	Category FHG—Housing	2	Series Number 508—Pitch5.08mm	3	Distinction No. 03	4	Row Option Single Row	5	Circuits XX
6	Entry Type M—Male	7	Material—Resin 2—PA66	8	Color—Resin T—Transparent	9	Packaging B—PE Bag		



 THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 18/JUN/13	PART NO. FHG50803-SXXM2TB	ITEM NO. FHG50803	 3K-KAMING	
	DESIGN UNITS Inch (metric)	X.X±.012(0.30)	X.±5'	CHECKED BY JACOB	DATE 18/JUN/13	TITLE Wire to Board Pitch 5.08mm(Housing)		REV 0
SCALE 5:1	SIZE A4	X.XX±.006(0.15)	.XX±1'	DRAWN BY CHERRY	DATE 18/JUN/13	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO DONG GUAN LANG LUN(3K-KAMING) ELECTRONIC PRODUCTS CO.,LTD. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		