

REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

Products Categories: A,B,C		
Part No.: FDBXX08-F0TS000XXKA	Part No.: FDBXX08-F0TS000XXKB	Part No.: FDBXX08-F0TS000XXKC
A Type	BACK NUT H=0.157in(4.0mm) B Type	FORMER NUT H=0.157in(4.0mm) C Type

Circuits (n)	Part No.	Dimensions(in/mm)				
		A	B	C	D	E
09	FDB0908-F0TS000XXKX	0.643(16.33)	.984(24.99)	1.216(30.80)	0.750(19.28)	0.610(15.50)
15	FDB1508-F0TS000XXKX	0.971(24.66)	1.311(33.30)	1.541(39.15)	1.085(27.55)	0.974(24.75)
25	FDB2508-F0TS000XXKX	1.511(38.38)	1.852(47.04)	2.089(53.04)	1.624(41.25)	1.496(38.00)
37	FDB3708-F0TS000XXKX	2.157(54.80)	2.502(63.55)	2.729(69.32)	2.260(57.40)	2.134(54.20)



Ordering Information

FDB	XX	08	-	F0	T	S	0	00	XX	K	X
1	2	3	4	5	6	7	8	9	10	11	

1	Category FDB- D-SUB	2	Circuits 9,15,25,37	3	Distinction No. 08	4	Type F0-Female	5	Assembly Layout T-Terminal Type	6	Entry Angle S-180° Vertical
7	Plating 0	8	Thickness of Plating 00	9	Color-Resin K6-Black U1-Blue	10	Packaging K-Tray	11	Products Categories A-A Type B-B Type C-C Type		

SPECIFICATIONS

Housing: PBT UL 94V-0
Shell: SPCC/Nickel Plated .
Temperature Range-Operating: -25°C~+105°C

 THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 28/JUN/13	PART NO. FDBXX08-F0TS000XXKX	ITEM NO. FDBXX08-F0	 3K-KAMING®	
		X.±.012(0.30)	X.±5°	CHECKED BY	DATE	TITLE			
DESIGN UNITS Inch (metric)		X.X±.008(0.20)	X.±2°	JACOB	28/JUN/13	D-SUB FEMALE TERMINAL TYPE CONN		REV 0	SHEET NO. 1/1
SCALE 5:1	SIZE A4	X.XX±.006(0.15)	.XX±1°	DRAWN BY	DATE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO DONG GUAN LANG LUN(3K-KAMING) ELECTRONIC PRODUCTS CO.,LTD. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
		X.XXX±.004(0.10)	.XXX±0.5°	CHERRY	28/JUN/13				