

1	2	3	4	5	6	7	8
REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD		





Table 1

Part No.:FDB3006-FFDB3XXK6LA A Type	Part No.:FDB3006-FFDB3XXK6LB B Type
Part No.:FDB3006-FFDB3XXK6LC C Type	Screws .187(4.75) .465(11.80) .189(4.80)



Recommended P.C.Board Layout

Ordering Information

FDB	30	06	-	FF	D	B	3	XX	K6	X	X
1	2	3	4	5	6	7	8	9	10	11	

SPECIFICATIONS

Electrical

- 1.Current Rating:3A AC(rms)/DC
- 2.Voltage Rating:250V AC(rms)/DC
- 3.Contact Resistance:25 mΩ Max
- 4.Insulation Resistance:1000 MΩ MIN
- 5.Withstanding Voltage:500V AC r.m.s
- 6.Temperature Range-Operating:-55℃~+105℃

Material and Finish

- 1.Housing: LCP OR PBT+30% UL 94V-0
- 2.Contact:Copper Alloy/Gold Flash Plated On Contact Area Tin Plated On Solderails,Nickel Under Plated Over All/Gold Plated Options
- 3.Shell: Spcc/Nickel Plated Over All
- 4.Board Lock: Copper Alloy/Tin Plated Over All
- 5.Screws: Copper Alloy/Nickel Plated Over All

1 Series Name FDB- D-SUB	2 Circuits 30	3 Distinction No. 06	4 Type FF-Female+Female	5 Assembly Layout D-DIP	6 Entry Type B-Side Entry Type
7 Plating 3-Half Gold/Tin	8 Thickness of Plating 00-Gold Flash 03-3u" Custom Plate Available	9 Plastic Colour K6-Black	10 Packaging L-PE Pipe K-PE Tray	11 Products Categories A-A Type B-B Type C-C Type	

 THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 28/JUN/13	PART NO. FDB3006-FFDB3XXK6LX	ITEM NO. FDB3006	 3K-KAMING	
DESIGN UNITS Inch (metric)		X.±.012(0.30)	X'±5"	CHECKED BY JACOB	DATE 28/JUN/13	TITLE D-SUB 15PIN FEMALE+15PIN FEMALE CONN			
SCALE 5:1	SIZE A4	X.XX±.006(0.15)	.XX'±1"	DRAWN BY CHERRY	DATE 28/JUN/13	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO DONG GUAN LANG LUN(3K-KAMING) ELECTRONIC PRODUCTS CO.,LTD. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

